



FLOOR GROMMETS

perfectly balancing

capacity & size

ACCESS GROMMETS

The Electrak range of simple-to-install access grommets allow cables and conduit to link between underfloor power and desk power systems.

- Ranging from 144mm to 232mm in diameter
- 169mm diameter grommet can accommodate up to 3 x 32mm conduits - perfectly balancing capacity and size
- Push-fit lid with optional screw fixing to prevent unauthorised access



POWER AND DATA GROMMETS

The Electrak range of cleaner's grommets are the latest addition to its power and data grommets range. Within their 169mm diameter, the grommet can house a flat RCD socket and provide ample space for the user to plug in or unplug equipment.

- Cleaner's grommet with flat mounted RCD socket or standard socket options
- Push-fit lid with cable flap feature
- Spring loaded screws for rapid installation
- Available pre-wired to powertrack tap-off



- 1 Removable inlay for optional carpet fitting
- 2 Cable flap allows permanent connection of services
- 3 Flat mounted RCD socket

- 4 169mm diameter provides the perfect balance between size and capacity
- 5 Spring loaded screws for rapid installation
- 6 Available pre-wired to powertrack tap-offs

floor grommets

access / power and data



Dimensions and technical information p. 35

Pack	Cat. Nos.	Plastic access grommets	Pack	Cat. Nos.	Plastic power and data grommets
1	EG0010	<p>Quick fit installation Precision engineered from hard wearing durable ABS Grey mouldings. Other colours available to special order Conform to IEC-61534-22 Simply secured by pushing down the spring-loaded screws and rotating a quarter turn</p> <p>144 mm Ø – cut-out size 127 mm Ø</p> <p>Can accomodate all cable types or three metal conduits up to a 20 mm Ø or 25 mm without foam</p>	1	EG0040	<p>169 mm Ø – cut-out size 152 mm Ø</p> <p>Quick fit installation Precision engineered from hard wearing durable ABS Grey mouldings. Other colours available to special order. Conform to IEC-61534-22 Removable carpet recess Cable flap feature so grommet lid can be closed while in use Simply secured by pushing down the spring-loaded screws and rotating a quarter turn</p> <p>13 A power grommet Supplied complete with 13 A unswitched socket</p>
1	EG0030	<p>169 mm Ø – cut-out size 152 mm Ø</p> <p>Allows power, data and flexible conduit up to 32 mm to pass through raised access floor Lid can be locked with screw (included) Maximum number of conduits : 9 x 20 mm Ø 5 x 25 mm Ø 3 x 32 mm Ø</p>	1	EG0045	<p>RCD power grommet Supplied complete with 13 A RCD socket</p>
1	EG0055	<p>232 mm Ø – cut-out size 215 mm Ø</p> <p>High capacity grommet Recommended for installation in light traffic areas</p>	1	EG0051	<p>13 A power/data grommet Supplied complete with 13 A socket and 1 x 37 x 22 mm cut-out</p>
1	EG0015	<p>Aluminium access grommet</p> <p>Body – cast aluminium Lid – injection moulded plastic Nylon 66 with neoprene cable gasket Secured by quarter-turn fasteners Floor depth 25 to 55 mm Access grommet depth 60 mm (95 mm when back box included)</p> <p>144 mm Ø – cut-out size 127 mm Ø</p> <p>Allows power, data and flexible conduit up to 25 mm to pass through raised access floor</p>	1	EG0052	<p>Data grommet Supplied complete with data plate 2 x 37 x 22 mm cut-out</p>
1	EG0025	<p>Aluminium power grommet</p> <p>13 A power grommet Supplied complete with 13 A switched socket</p>	1	EG0041	<p>Pre-wired power grommets</p> <p>169 mm Ø – cut-out size 152 mm Ø</p> <p>Cleaners socket version</p> <p>DP1332 - 3 m unfused DP1532 - 5 m unfused DP1313 - 3 m 13 A fused DP1513 - 5 m 13 A fused</p>
			1	EG0042	DP1532 - 5 m unfused
			1	EG0043	DP1313 - 3 m 13 A fused
			1	EG0044	DP1513 - 5 m 13 A fused
			1	EG0046	DP1332 - 3 m unfused
			1	EG0047	DP1532 - 5 m unfused
			1	EG0048	DP1313 - 3 m 13 A fused
			1	EG0049	DP1513 - 5 m 13 A fused


floor grommets

technical information

■ 144 mm Ø plastic floor grommet

Dimensions

Cat. No. EG0010




■ 169 mm Ø plastic floor grommets


Dimensions

Access grommet

Cat. No. EG0030



Power grommet




Recommended hole cutter is a 6 1/8 inch hole saw blade

■ 232 mm Ø plastic floor grommet

Dimensions

Large quick fit grommet
Cat. No. EG0055



Floor panel cut-out diameter

Recommended hole cutter is a adjustable hole saw blade with Ø range of 40 mm - 300 mm

■ To install plastic floor grommets

A



Lift handle and pull to remove lid

B



Push grommet into raised floor tile aperture
Push down spring loaded screws and rotate quarter turn to secure
Ensure wings are located under floor panel
For honeycombed floor panels one wing should face downwards and one wing should face upwards

C



Cable access insert
Drop cable access insert into housing opening

D



Slide lid into lug holes



E



(1) Push down lid to close
(2) If grommet is not in use, replace cable access insert



■ 144 mm Ø aluminium grommets

Access grommet



Cat. No. EG0015

13 A power grommet



Cat. No. EG0025

Recommended hole cutter is a 5 1/16 inch hole saw blade